

WHITE HOT 🎹

Product Description

EXTREME White Hot[™] is an adhesive designed specifically for use in joining PVC (Poly Vinyl Chloride) plastic to itself. EXTREME White Hot[™] is a fast acting, high strength adhesive.

Application Data

EXTREME White HotTM is to be used as supplied in its original container. The surfaces to be adhered should be clean and free of dirt, oil, moisture, ect. Apply **EXTREME White Hot**TM to the complete surface of the material being joined. Follow safety precautions during use. Hold parts together mechanically while adhesive is curing. Allow 24 hours drying at room temperature before testing.

Safety Precautions

EXTREME White HotTM is extremely flammable and should not be used or stored near heat, sparks or flame. It should be used only in a well-ventilated area. Avoid prolonged breathing if vapor or contact with skin and eyes. Keep tightly closed when not in use and covered as much as possible when using. In case of contact with eyes, immediately flush with plenty of water for 15 minutes and get medical attention. If swallowed, drink water, do not induce vomiting, and call a physician. Keep out of reach of children.

Technical Data

Color	White
Density	8lbs/gal
Body	Extra Heavy Body
Flashpoint	6°F (Closed Cup)

EXTREME White Hot™ contains a UV Protectant

Shelf Life: 1 Year Minimum

Limited Warranty: Our warranty is limited to replacement or credit for defective material. It is the responsibility of user to determine the suitability of this product for their application.

Part Number: EXT-WHOT-5OZ & EXT-WHOT-10OZ

Contact an **EXTREME ADHESIVES**[®] Adhesive Applications Specialist for further recommendations on adhesive selection.

The properties represented herein are TYPICAL VALUES and not intended for use in specifications. *Extreme Adhesives, Inc.* MAKES NO EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS OR OTHERWISE. While the information presented is believed to be accurate, no warranty or recommendation is made as to application. Determination of product suitability is the sole responsibility of the user. Suggestions made do not constitute any guarantee in as much as use conditions are beyond our control.