Jain Irrigation Systems Ltd.

Jain Plastic Park, N.H.6, Bambhori, Jalgaon 425 001 (India) Tel : + 91 (0) 257 225 00 11 Fax : + 91 (0) 257 225 11 11



Fax : + 91 (0) 257 225 11 11			
SDS Number 16275040	FF Edition: 04	Revision : 00	Date : 01.10.201
1. Identification			
(a) Product Identifie	er EX-CEL PVC Fr	ee Foam Sheet	
(b) Other means of identification	Not provided		
(c) Use of the Product	No additional inf	formation provided	
(d) Name, Address			
and Telephone		k, N.H. No : 6, Bambhor	ï
number of the	Jalgaon 425001		
Manufacturer (e) Emergency	Tel : +91 257 22 +91 257 225801		
phone number	+91 237 223001	1 / 22	
2. Hazard(s) Ident			
(a) Classification of	the Product		
Not Classified	Due du et		
	(b) Labelling of the Product		
(c) Other Hazards	Not applicable		
	(c) Other Hazards EXCEL PVC Free Foam sheet is produced by extrusion process from Polyvinyl chloride		
			extrusion process. These additive
and Polyvinyl c	hloride polymer are	all in a homogenous fu	used state and after formation int
			et is subjected to extreme heat of
			ring the fabrication work such a
			generation of dust and if this dua n. Appropriate Personal Protectiv
			recautionary efforts shall be take
	dust generation.	ska andi be used and p	recationary enorts shall be take
(d) Unknown acute			
Data not available			
3. Composition / I		gredients	
(a) Substance	Not Applicable		
(b) Mixture	040 N		
Material	CAS No	Percentage	Classification

		0	
Polyvinyl chloride	9002 - 86 - 2	> 70 %	Combustible dust
Calcium carbonate	1317 – 65 – 3	< 5 %	No classification
Titanium dioxide	13463 – 67 - 7	< 5 %	Carc.2 H351
EXCEL PVC Free Foam sheet is produced from Polyvinyl chloride polymer and various additives as			

EXCEL PVC Free Foam sheet is produced from Polyvinyl chloride polymer and various additives as required for the extrusion process. Above health hazards is given for individual component of the additives and this is not applicable to the final product as all Polyvinyl chloride and additives are fully fused & homogenized.

4. First Aid Measures	
(a) Description of First aid measures for different routes of exposure	Inhalation : If smoke from burning plastics is inhaled, remove and subject to fresh air immediately. If any symptoms develop seek immediate medical attention. Skin : If burnt by molten plastics sheet get medical attention immediately. Eye : Immediately flush eyes with water for atleast 15 minutes. Do not rub the eyes. If irritation develops consult a physician. Ingestion : Quite unlikely. In case ingested rinse the mouth and contact medical attention.
(b) Most important symptoms / effects, acute and delayed	Product as such does not pose any health hazard. During fabrication it quite likely that there will be dust generation. This dust may cause irritation to the eyes, nose and throat. Sheet edges may be sharp and may cause injury if handled with bare hand. Molten sheets may generate fumes and if comes in contact with skin or body may cause thermal burn. If exposed to dust of sheets or fumes of burnt sheets immediately seek medical attention.
(c) Indication of any medical attention and special treatment needed	If exposed to dust of sheets or fumes of burnt sheets immediately seek medical attention.

5. Fire Fighting Measures

Extinguishing media	Dry chemical, carbon dioxide, foam water. Avoid use of heavy	
	stream of water.	
Specific hazards arising from	Product does not catch fire. But at high temperature it may degrade	
the chemical	to liberate gases and fumes.	
Special protective equipment and precautions for fire fighters	Wear respiratory masks, Full protective clothing, gloves and other appropriate protective equipment in case of fire. Evacuate all personnel from danger area. Use dry chemical, foam water or carbon dioxide to extinguish fire.	

6. Accidental release measures

(a) Personnel precautions, protective equipment and emergency procedures Avoid generating dust during fabrication. Wear respiratory masks to avoid dust inhalation. Contact with eyes, skin to be avoided. Ignition source to be removed Sheets shall be kept away from direct heat, flames, hot surfaces and any other ignition sources. Wear appropriate personal protective equipment and evacuate the area in case of any fire related emergency. In case of fire ventilate and secure the area. If required, call for trained assistance.

(b) Methods and materials for containment and cleaning up

Collect and segregate the solid spills over from the sheets after fabrication work. Do not allow it to get into the sewer or water stream line. Clean spills immediately after the work and take up mechanically for collection in a suitable container for final disposal. For cleaning and collecting the dust on floor use vacuum cleaner which is explosion proof. Avoid mixing with other plastic or non plastic materials.

7. Handling and storage		
(a) Precautions for safe handling	Wear safety glasses during sheet cutting or fabricating process. Wear gloves during fabrication work. Avoid any ignition source during the fabrication work as it can lead to combustible dust explosion. Wash hands thoroughly with soap solution before eating, drinking, smoking or leaving the work. Avoid eyes, skin and cloth contact with the dust. Do not inhale the dust. Avoid smoking while working with the sheets. Avoid sparks, light or heat source, open flames, hot surfaces.	
(b) Conditions for safe storage, including any incompatibilities	Avoid creating dust and use explosion proof electrical and lighting equipment. Avoid generation of static electric charge and use proper grounding procedures. Store in a cool, dry and well-ventilated area. Avoid outdoor storage and storage under direct sunlight. Sheet is incompatible to strong and concentrated acids, bases, strong oxidizing agents / chemicals.	
8. Exposure controls /	nersonal protection	
Polyvinyl Chloride - CAS number : 9002 – 86 – 2	Exposure limit : TLV (ACGIH – USA) 1 mg / m3 Respirable PNOC. ACGIH Chemical category – not classified as human carcinogen	
Calcium Carbonate - CAS number : 1317 – 65 - 3	Exposure limit : NIOSH REL (TWA) : 10 mg / m3 total dust & 5 mg / m3 respirable dust. PEL (OSHA) : 15 mg / m3 total dust & 5 mg / m3 respirable dust	
Titanium dioxide - CAS number : 13463 – 67 – 7	Exposure limit : TLV (ACGIH – USA) 10 mg / m3 ACGIH Chemical category – not classified as human carcinogen. PEL (OSHA) : 15 mg / m3 total dust	
 (b) Appropriate engineering controls (c) Individual protection measures (Personal protection equipment) 	If the product is cut or fabricated there exists possibility for dust or particulate matter generation. For emergency eye wash & safety showers shall be made available. Provide adequate ventilation in work area. Avoid static electricity through proper grounding procedures. Use explosive proof equipment in work area and dust shall be collected to avoid dust in work area. Avoid any live flames, ignition source or hot surfaces to avoid combustible dust generation. Adhere to national or local regulations. Sheet edges may be sharp and use appropriate gloves. Wear respiratory masks, full clothing during fabrication work. Wear protective goggles.Cloth shall be chemical resistant. Do not eat, smoke or drink while working with the sheets	
9. Physical and chemic		
 (a) Appearance (b) Odour (c) Odor threshold (d) pH (e) Melting point / freezing point 	Solid No data available No data available Not applicable No data available	
 (f) Initial boiling point and boiling range (g) Flash point (h) Evaporation rate (i) Flammability (Solid / 	Not applicable No data available Not applicable No data available	
gas) (j) Upper / lower flammability or explosive limits	No data available	
 (k) Vapor pressure (l) Vapor density (m) Relative density (n) Solubility (o) Partition coefficient : 	No data available No data available No data available No data available No data available	

	n-Octanol / water	
(p)	Auto ignition	No data available
	temperature	
(q)	Decomposition	No data available
	temperature	
(r)	Viscosity	Not applicable

10. Stability and Reactivity		
Reactivity	Product is stable under normal conditions	
Chemical stability	Product is stable if stored and handled properly as highlighted in point 7.	
Possibility of hazardous reactions	No hazardous reactions will occur. Product is stable.	
Conditions to avoid	Avoid direct sunlight, extreme high temperature, static electricity, ignition source, hot surface, open flame, sparks, heat and contact with incompatible materials. Avoid accumulation of dust during fabrication to avoid dust explosion hazard	
Incompatible materials	Strong or concentrated acids, bases, oxidizing chemicals, halogens.	
Hazardous decomposition products	Product may undergo thermal degradation and emits carbon dioxide, carbon dioxide, hydrogen chloride, Irritating fumes and black fumes.	

11. Toxicological Information

The Toxicological Information			
(a) Information on the likely routes of exposure (inhalation, ingestion, skin and eye	Dust may be harmful or cause irritation to skin or eye. May cause allergy to sensitive individual if the dust or particulate matter is ingested.		
contact)			
(b) Symptoms related to physical, chemical and toxicological characteristics	Dust may cause irritation to eyes and after inhalation. Prolonged exposure may cause skin irritation.		
(c) chronic effects	None known.		
(d) Numerical measures of toxicity	None known.		
(e) whether hazardous chemical is listed in NTP report on carcinogens or has been found to be potential carcinogen in IARC or by OSHA	None.		

12. Ecological Information	
(a) Ecotoxicity	Not classified
(b) Persistence and	Not established
degradability	
(c) Bioaccumulative potential	Not established
(d) Mobility in soil	Not available
(e) Other adverse effects such	None
as hazardous to the ozone	
layer	

13. Disposal considerations

Disposal recommendations	Dispose of in accordance with local, national and international
•	regulations.
Additional information	Recycle the product after intended use as far possible
14. Transport informati	on
	ccordance with DOT, IMDG and IATA.
5	
15. Regulatory Informa	tion
Federal Regulatory Information	
OSHA Status	Not listed, non-hazardous
EPA Clean Air Act Status	Not listed
EPA Clean Water Act Status	Not listed
TSCA Status	Polyvinyl chloride, Lime stone, Titanium dioxide are all listed on TSCA inventory (40 CFR710)
CERCLA RQ	Not listed
SARA Title III : PVC Sheet	-
Section 302*	None * Reportable quantity of extremely hazardous
	substance, Sec 302
	Threshold planning quantity, extremely hazardous
	substance. Sec. 302
Section 313**	None ** Toxic Chemical Sec. 313
	** Category as required by Sec. 313 (40CFR37263 C) must be used
Section 311/312***	on Toxic Release Inventory form None *** Hazard category for SARA Sec. 311/312 reporting
Section 311/312	H1= acute health hazard
	H2= chronic health hazard
	P3= fire hazard
	P4= sudden release of pressure hazard
	P5= reactive hazard
RCRA Status	It is the responsibility of the product user to determine at the time of
	disposal whether a material containing the product or derived from
	the product should be classified as a hazardous waste (40CFR261.
	20-24)
	including date of preparation or last revision
Revision Date	1 st October 2016
Other information	This document has been prepared in accordance with the SDS
	requirements of the OSHA Hazard communication standard 29 CFR 1910.1200
NFPA	HMIS
Fire – 1	Health - 0
Health – 0	Flammability – 1
Reactivity – 0	Reactivity – 0
Specific Hazard - None	Personal Protection Index - E

This information is furnished without warranty, expressed or implied except that it is accurate to the best knowledge of Jain Irrigation Systems Ltd., Neither Jain Irrigation Systems Ltd., nor any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. Jain Irrigation Systems Ltd., assumes no legal responsibility for loss, damage or expense arising out of, or in any way connected with the handling, storage, use or disposal of this product.